

PRODUCT SPECIFICATIONS




Alubrite® (Code 7070) is an A1 Non-Combustible product and consists of aluminium foil on both sides with a reinforced scrim in middle laminated with flame retardant adhesive.

ARCHITECTURAL SPECIFICATION

Alubrite® (Code 7070) Non-Combustible A1 radiant barrier. Use in conjunction with Galvanised straining wires 275mm apart and 24mm D/s Tape.

TECHNICAL INFORMATION	ROLL
Appearance	SILVER
Length	40M
Width	1250MM
Roll Size	50M ²
Effective Coverage	44M ²
Overlap	150MM
*System Thermal Resistance SANS 8301:2010 (Reflective Foil Laminates – Rolls, Sheets And Sections)	1.91m ² .K/W.
Fire Rating: SANS 428 (SANS 10177-5 & SANS 10177-10)	A/A1/1
Mass Per Unit Area G/M ²	140g/m ²
Weight per roll	7.44kg
Tensile Strength N/25mm-Md	419
Tensile Strength N/25mm-Xd	307
Bursting Strength N/Cm ²	42
NEW FIRE RATING SANS 53501-1 (EN 13501-1)	A2-s1, d0

* Product was tested with air gaps of 40mm at the top (Hot side) and 60mm at the bottom (Cold side)



ATI

AFRICA THERMAL INSULATIONS
A DIVISION OF WEST RAND ENGINEERING